

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A method for installing software to software-defined radio equipment comprising the steps of:
transferring software to a software-defined radio device from a software server, said software server remotely located with respect to said software-defined radio device;
storing said software to a portion of a data store associated with said software-defined radio device, said portion of said data store not being used as a storage for currently running software;
transferring a selection specifying whether the transferred software or the currently running software will be loaded ~~identifying at least one of said transferred software and said currently running software to be loaded~~ by said software-defined radio device during a restart of said software-defined radio device; and
loading the selected software ~~at least one of said transferred software and said currently running software~~ to said software-defined radio device during a restart of said software-defined radio device.
2. (Currently Amended) The method according to claim 1, further comprising the step of automatically reverting to a previous software version upon a fault detection in loading the selected software ~~at least one of the transferred software or said currently running software~~.
3. (Original) The method according to claim 1, further comprising the step of monitoring said transferring and loading steps.
4. (Cancelled)
5. (Cancelled)

6. (Currently Amended) The method according to claim [[4]] 1, wherein said selection identifies a software version.
7. (Original) The method according to claim 1, further comprising the steps of: transferring said transferred software to at least a second software-defined radio device; and
consecutive with said loading step, loading said transferred software to said second software-defined radio device.
8. (Original) The method according to claim 1, further comprising the step of providing an error indication if a fault is detected in at least one of said transferring step and said loading step.
9. (Original) The method according to claim 1, wherein said transferred software comprises a plurality of software components.
10. (Original) The method according to claim 1, further comprising the step of providing a version indicator accessible from a remote location, said version indicator identifying software which is currently loaded on said software-defined radio device.
11. (Original) The method according to claim 1, further comprising the step of providing a software listing accessible from a remote location, said software listing identifying software currently available on said data store.
12. (Original) The method according to claim 1, wherein said storing step comprises storing said transferred software to a second data store associated with said software-defined device.
13. (Original) The method according to claim 12, wherein said second data store is non-volatile.
14. (Original) The method according to claim 1, wherein said transferring step occurs while said software-defined radio device continues to perform software-defined radio functions.

15. The method according to claim 1, wherein said software server is a computer operatively connected to said software-defined radio device via a communications network.
16. (Currently Amended) A method for installing software to software-defined radio equipment comprising the steps of:
 - receiving to a software-defined radio device software from a software server, said software server remotely located with respect to said software-defined radio device;
 - storing said software to a portion of a data store associated with said software-defined radio device, said portion of said data store not being used as a storage for currently running software;
 - specify whether the transferred software or the currently running software will be loaded
 - receiving to said software-defined radio device a selection specifying whether the transferred software or the currently running software will be loaded ~~identifying at least one of said transferred software and said currently running software to be loaded~~ by said software-defined radio device during a restart of said software-defined radio device;
 - loading the selected ~~said at least one of said transferred software and said currently running~~ software; and
 - verifying said loading step.
17. (Currently Amended) The method according to claim 16, further comprising the step of automatically reverting from the selected software ~~said at least one of said transferred software and said currently running software~~ to a previous software version upon a fault being detected in said loading step.
18. (Original) The method according to claim 16, further comprising the step of providing an error indication upon said fault detection.
19. (Original) The method according to claim 16, further comprising the steps of: monitoring said receiving step; and
 - providing an error indication if a fault is detected in said receiving step.

20. (Original) The method according to claim 16, further comprising the step of providing a version indicator accessible from a remote location, said version indicator identifying software which is currently loaded on said software-defined radio device.
21. (Original) The method according to claim 16, wherein said selection identifies a software version.
22. (Original) The method according to claim 16, further comprising the step of providing a software listing which is accessible from a remote location, said software listing identifying software currently available on said data store.
23. (Original) The method according to claim 16, wherein said storing step comprises storing said transferred software to a second data store associated with said software-defined device.
24. (Original) The method according to claim 23, wherein said second data store is non-volatile.
25. (Original) The method according to claim 16, further comprising the step of decompressing said transferred software after said receiving step.
26. (Original) The method according to claim 16, wherein said receiving step occurs while said software-defined radio device continues to perform software-defined radio functions.

27. (Currently Amended) A system for installing software to software-defined radio equipment comprising:
- a software server for transferring software to a software-defined radio device from a location remotely located with respect to said software-defined radio device;
 - a man-machine interface associated with said software server for receiving from a system operator a selection specifying whether the transferred software or the currently running software will be loaded ~~identifying at least one of said transferred software and said currently running software to be loaded~~ at a next startup of said software-defined radio device;
 - a data store associated with said software-defined radio device for storing said software, said software stored on a portion of said data store which is not being used to provide currently running software; and
 - a processor programmed to:
 - load ~~[[a]]~~ the selected software ~~one of said transferred software and said currently running software~~ to said software-defined radio device during a restart of said software-defined radio device; and
 - automatically revert from the selected software ~~said selected one of said transferred software and said currently running software~~ to a previous software version if a fault occurs in said loading of said selected software.
28. (Original) The system according to claim 27, wherein said processor is further programmed to monitor said transferring of said software, and loading of said selected software.
29. (Original) The system according to claim 27, wherein said software server transfers said transferred software to at least a second software-defined radio device, wherein said transferred software is consecutively loaded on said software-defined radio device and on said second software-defined radio device.
30. (Original) The system according to claim 27, wherein said software server further comprises a compression application for compressing said software prior to said software being transferred.

31. (Original) The system according to claim 27, wherein said transferred software comprises a plurality of software components.
32. (Original) The system according to claim 27, wherein said man-machine interface further comprises a version indicator, said version indicator identifying software which is currently loaded on said software-defined radio device.
33. (Original) The system according to claim 27, wherein said man-machine interface provides a software listing identifying software currently available on said data store.
34. (Original) The system according to claim 27, further comprising a second data store associated with said software-defined device for storing said transferred software.
35. (Original) The system according to claim 34, wherein said second data store is non-volatile.
36. (Original) The system according to claim 27, wherein said software is transferred to said software-defined radio device while said software-defined radio device continues to perform software-defined radio functions.
37. (Previously Presented) The system according to claim 27, wherein said software server is a computer operatively connected to said software-defined radio device via a communications network.
38. (New) A method for installing software to software-defined radio equipment comprising the steps of:
 - transferring software to a software-defined radio device from a software server, said software server remotely located with respect to said software-defined radio device;
 - storing said software to a portion of a data store associated with said software-defined radio device, said portion of said data store not being used as a storage for currently running software;

transferring a selection specifying whether the transferred software or the currently running software will be loaded by said software-defined radio device during a restart of said software-defined radio device.